


DS-PDBG8-EG2

- High quality Omni-directional microphone sensor
- Up to 8m/120° detection coverage
- Selectable EOL resistors (Alarm Resistance: 1K, 2K2, 4K7, 5K6, 6K8)
- 9-16 VDC wide voltage adaptation with polarity reverse connection protection



▪ Specification


Detection Performance	
Detection Method	Acoustic Sensor
Detection Range	8 m
Detection Angle	120°
Glass Break Sensitivity	Potentiometer Adjustment
Glass Type	Float, Plate, Tampered, Wired, Laminated Leaded, Double Glazing
Glass Thickness	2.4 mm to 6.4 mm
Glass Size	0.3 m x 0.3 m to 3 m x 3 m
Feature	
Digital Processing	Support
Tamper Protection	Front
Interface	
Alarm Output	Normally Closed
LED Indicator	Red(High Frequency Trigger), Green(Low Frequency Trigger), Blue(Alarm)
Transmission	
Transmission Method	Wired
Electrical Characteristics	
Power Supply	9-16 VDC
Typical Voltage	12 V
Power Consumption	25 mA
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	38.8 mm × 107 mm × 22.5 mm
Weight	49.5 g
Mounting Method	Wall, Ceiling
Application Scenario	Indoor

▪ Available Model


DS-PDBG8-EG2

▪ Installation

Choose the right location



Properly test the detector after installation



Note:

You should use the matching tester.

Warning:

1. Avoid mounting the detector on the same wall as the protected glass.
2. Avoid mounting the detector in rooms with noisy equipment (air compressors, power tools, bells, etc.)
3. Avoid mounting the detector in humid rooms (bathroom, etc.)
4. Avoid mounting the detector on the wall with strong vibration.

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com