

DS-PM501R4

Bus Relay Expander



DS-PM501R4 is a wired 4-way power relay expander. Each relay can handle current of 5A 30VDC, 16A 230VAC, which is enough to connect a very power-hungry device.

- Supports 4 onboard power relays, each relay can handle current of 5A 30VDC, 16A 230VAC
- Support extend bus distance

▪ Specification

Hardware features	
Tamper-Proof	Front and Rear
Bus	1 input for control panel connection and 1 output for bus extender
IO output	4 Relay output(5A 30VDC, 16A 230VAC)
Electrical characteristics	
Power supply	9-16VDC, provided by bus
Power consumption	300 mA @12VDC (Maximum Current) 200 mA @12VDC (Quiescent Current)
Output voltage	9-16VDC
General	
Dimension (W×H×D)	110 × 155 × 31 mm
Shell material	plastic
Color	white
Weight	272 g
Operation temperature	-20°C to 60°C (-4°F to 140°F)
Operation humidity	10% ~ 90% noncondensing

▪ Running Environment

▪ Available Model

DS-PM501R4

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq